



GENERAL		COMMUNICATIONS EQUIPMENT	
Place of Build	Fujian South East Shipyard, China	HF radio	FURUNO RC-1500-1T 400W
Vessel Type	AHTS	VHF Radio	2 x FURUNO
Year Built	2012	Portable VHF Radio's	3 x FURUNO
Flag	Singapore	Satellite Communications (Voice and Fax)	V-SAT
Call Sign	9V9838	E.P.I.R.B	McMurdo 406
Class	ABS FIFI 1 DPS 1, Oil Rec Class 2	GMDSS Compliance	Area A3
PRINCIPAL DIMENSIONS		NAVIGATION EQUIPMENT	
Length Overall	59.25 metres	Radar No. 1	Furuno x-band (21" screen)
Beam	14.95 metres	Radar No. 2	Furuno x-band (15" screen)
Maximum Draft	4.95 metres	GPS	GP 150
Net Registered Tonnage	503	Echo Sounder	Furuno FE 702
Gross Registered Tonnage	1678	Navtex	NX 700
		Auto Pilot	Naupilot NP 60
		Gyro Compass	Anchutz STD 22
		DP System	Kongsberg
MACHINERY & PROPULSION		DECK MACHINERY	
Main Propulsion Number	2	Tugger Winch	2 x 10 tons @ 15m/min
Main Propulsion Type	CAT 3516B Diesel	Capstan	2 x 5 tons @ 15m/min
Total BHP	5150	Deck Crane	1 x 3 tonnes @ 9 m
Propellers	2 x CPP in Fixed Kort Nozzles		
Bow Thruster	1 X Kawasaki KT-72B3 - 515KW		
	8 TONS		
Stern Thruster	1 x Kawasaki KT-55B3 - 390KW		
	6 TONS		
Main Generators	2 x CAT C18 350KW	TOWING & ANCHOR HANDLING	
Shaft Generators	2 x 800KW	Bollard Pull	67.9 Tons
Emergency Generators	1 x CAT 65KW	Winch	Plimssoll Waterfall Type
Rudders	Standard	Line Pull	150 tons
		Brake Capacity	200 tons
PERFORMANCES		Anchor Handling Wire and Towing Wire	100m and 1000m x 56mm
Fuel Consumption at Max Speed	18 m3 per day @ 13 knots	Anchor Handling Wire Capacity	100 m x 56 mm
Fuel Consumption at Service Speed	10 m3 per day @ 10 knots	Tow Drum Capacity	1000 m x 56 mm
Towing	20 m3 per day	Spare Tow Wire Capacity	1000 m x 56 mm
Standby	1 m3 per day	Stern Roller	4.0 m x 1.6 m - SWL 200 tonnes
Fuel Type	ISO 8217: 2005 DMA or later revisions	Tow Pins	2 x Closed Top Type SWL 200T
CARGO CAPABILITIES		Shark Jaws	Shark Jaws - SWL 200T
Fresh Water	360 m3 @ 100m3 per hr at 75m head	LIFE SAVING APPARATUS	
Drill Water	400 m3 @ 100m3 per hr at 75m head	Liferafts	Total 6, capacity 150 men
Fuel Capacity (100%)	535 m3 @ 150m3 per hr at 75m head	Rescue Boat	15 HP OBM, capacity 6 men
Liquid Mud	378 m3 @ 70m3 per hr		
Dry Bulk	4 X 1650 cu ft each, total 6,600 cu ft	EXTERNAL FIRE FIGHTING	
Dead Weight	1360 tons	Capacity	FIFI 1 - 2 x 1200 cu m per hr
Clear Deck Area	340 Square Metres	Monitor	2
Deck Cargo	500 tons	Throw x Height	120 m x 50 m
ACCOMMODATION			
Crew	12		
Passengers	28		
	(1 x 2 berth) & (7 x 4 berth)		
	Total 40		

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented, no guarantees of accuracy can be given. For enquires, kindly email us at chartering@sg.vroonoffshore.com.