

**GENERAL**

Place of Build	Fujian South East Shipyard, China
Vessel Type	AHTS
Year Built	2011
Flag	Singapore
Call Sign	9V8732
Class	ABS FIFI 1 DPS 1

COMMUNICATIONS EQUIPMENT

HF radio	Furuno RC-1800T
VHF Radio	2 x Furuno FM-8800S
Portable VHF Radio's	3 x McMurdo R2 Handheld
Satellite Communications (Voice and Fax)	Mini M
E.P.I.R.B	McMurdo SMARTFIND E5
GMDSS Compliance	Area A3

PRINCIPLE DIMENSIONS

Length Overall	59.25 metres
Beam	14.95 metres
Maximum Draft	4.95 metres
Net Registered Tonnage	503
Gross Registered Tonnage	1500~

NAVIGATION EQUIPMENT

Radar No. 1	X-Band Furuno FAR-2117
Radar No. 2	X-Band Furuno FR-1510 MARK-3
GPS	GP 150
Echo Sounder	Furuno FE 700
Navtex	NX 700
Auto Pilot	Nautopilot NP 60
Gyro Compass	Anchutz STD 22
DP System	Marine Tech

MACHINERY & PROPULSION

Main Propulsion Number	2
Main Propulsion Type	CAT 3516B Diesel
Total BHP	5150
Propellers	2 x CPP in fixed nozzles
Bow Thruster	1 x electric motor, CPP
Lateral Thrust	6 tons
Auxiliary Generators	3 x 350 KW diesel driven
Emergency Generators	1 x 65kW diesel
Rudders	Standard

DECK MACHINERY

Tugger Winch	2 x 10 tons
Capstan	2 x 5 tons
Deck Crane	1 x 3 tonnes @ 9 m

PERFORMANCES

Fuel Consumption at Max Speed	approx 18 m3 per day @ 13 knots
Fuel Consumption at Service Speed	approx 10 m3 per day @ 10 knots
Towing	approx 20 m3 per day
Standby	approx 1 m3 per day
Fuel Type	ISO 8217: 2005 DMA or later revisions

TOWING & ANCHOR HANDLING

Bollard Pull	65 tons
Winch	Plimssoll Waterfall Type
Line Pull	150 tons
Brake Capacity	200 tons
Anchor Handling Wire Capacity	150 m x 52 mm
Tow Drum Capacity	1000 m x 52 mm
Spare Tow Wire Capacity	1000 m x 52 mm
Stern Roller	4.4 m x 1.6 m - SWL 200 tonnes
Tow Pins	2 x Karmoy pins
Shark Jaws	1 x Karmfork

CARGO CAPABILITIES

Fresh Water	300 m3 @ 100m3 per hr at 75m head
Drill Water	400 m3 @ 100m3 per hr at 75m head
Fuel Capacity (100%)	540 m3 @ 150m3 per hr at 75m head
Liquid Mud	385 m3 @ 70m3 per hr
Dry Bulk	4 X 1650 cu ft each, total 6,600 cu ft
Dead Weight	1400 tons
Clear Deck Area	320 Square Metres
Deck Cargo	500 tons
Deck Loading	7.5 tonnes/sqm

LIFE SAVING APPARATUS

Liferafts	Total 6, capacity 150 men
Rescue Boat	25 HP OBM, capacity 6 men

EXTERNAL FIRE FIGHTING

Capacity	FIFI 1 - 2 x 1200 cu m per hr
Monitor	2
Throw x Height	120 m x 50 m

ACCOMMODATION

Crew	12
Passengers	28
	(4 x 1-berth, 3 x 2-berth, 8 x 4-berth)
Total	40

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure that accuracy of the information represented within this document, no guarantees of accuracy can be given.

