



**IVER SHIPS B.V.** • E chartering@iverships.com • E operations@iverships.com • W www.iverships.com

# Great Eastern

<b>Builder</b> : Hyundai Mipo, S. Korea <b>Yard number</b> : 377 <b>Year built</b> : 2005 <b>Flag</b> : Marshall Islands <b>Port of Registry</b> : Majuro <b>IMO number</b> : 9298739			<b>Tonnages</b>			
				ITC69	Suez	Panama
			Gross tonnage	23,356	24,428	23,356
			Net tonnage	10,119	21,144	19,455
<b>Class notation</b>			<b>Tanks / Capacities</b>			
LR +100A1 Double Hull Chemical tanker Ship type 2 in association with an approved List of Defined Cargoes, ESP + LMC, UMC, Ice Class 1B FS at draught of 11.20 m, CG, IGS, LI, *IWS, ShipRight (SDA, FDA, CM) and SCM: COW IGS (LR) SBT/ PL			Tank	ManCon	98% capacity	Pump cap.
			1P	12"	3,002.8 m <sup>3</sup>	300 m <sup>3</sup> /hr
			1S	12"	3,007.9 m <sup>3</sup>	300 m <sup>3</sup> /hr
			2P	14"	3,582.1 m <sup>3</sup>	500 m <sup>3</sup> /hr
			2S	14"	3,584.2 m <sup>3</sup>	500 m <sup>3</sup> /hr
			3P	14"	3,593.4 m <sup>3</sup>	500 m <sup>3</sup> /hr
			3S	14"	3,594.7 m <sup>3</sup>	500 m <sup>3</sup> /hr
			4P	14"	3,593.7 m <sup>3</sup>	500 m <sup>3</sup> /hr
			4S	14"	3,597.1 m <sup>3</sup>	500 m <sup>3</sup> /hr
			5P	14"	3,593.8 m <sup>3</sup>	500 m <sup>3</sup> /hr
			5S	14"	3,597.6 m <sup>3</sup>	500 m <sup>3</sup> /hr
			6P	14"	3,298.0 m <sup>3</sup>	500 m <sup>3</sup> /hr
			6S	14"	3,297.0 m <sup>3</sup>	500 m <sup>3</sup> /hr
			Slop P	8"	334.8 m <sup>3</sup>	150 m <sup>3</sup> /hr
			Residual	5"	100.8 m <sup>3</sup>	70 m <sup>3</sup> /hr
			Slop S	8"	427.2 m <sup>3</sup>	150 m <sup>3</sup> /hr
			Total:		42,205.0 m <sup>3</sup>	
<b>Dimensions / Distances</b>			Number of cargo tanks: 12 Number slop tanks: 2 Number of D/V segregations: 7 Coating Type: Phenolic Epoxy			
LOA	: 182.55 m	598'11"				
Length between pp	: 175.00 m	574'2"				
Beam moulded	: 27.34 m	89'8"				
Depth	: 16.70 m	54'9"				
Maximum draft	: 11.22 m	36'10"				
Keel to top of mast	: 44.79 m	146'4"				
Bow to center manifold	: 92.04 m	185'4"				
Deck to manifold	: 2.10 m	6'11"				
Rail to manifold flange	: 4.34 m	14'3"				
<b>Deadweight</b>			<b>Remarks</b>			
Tropical fresh	: 11.70 m	38'5"	38,565 MT	Bowtruster : installed, 800 kW  <i>All particulars given in good faith, without guarantee</i>		
Fresh	: 11.47 m	37'8"	37,509 MT			
Tropical salt	: 11.45 m	37'7"	38,596 MT			
Summer	: 11.22 m	36'10"	37,520 MT			
Winter	: 10.98 m	36'0"	36,448 MT			
<b>Speed</b>						
Service speed: 14.7 knots						