



VOS PRIDE

Platform-supply vessel

KCM 80M

Vessel number 3251

GENERAL

Flag	Malaysia
Year built	2015
Place built	Fujian South East Shipyard, China
Class	LR A1 Offshore Supply Ship, Fire-Fighting Ship 1 (2400m ³ /h) with water spray, HNLS, oil recovery, IWS, WDL (t/m ² from aft to frame 71), ECO(TOC), LMC, UMS, DP(AA), SPS 2008
Call sign	9WNK4
ERN number	99.98.87.68
Vessel type	Platform Supply Vessel

PRINCIPAL DIMENSIONS

Length overall (LOA)	80 m
Breadth moulded	18.40 m
Design draft	6 m
Maximum draft	6.35 m
Net tonnage	1,196 t
Gross tonnage	3,548 t
Deadweight	3,830 t

MACHINERY & PROPULSION

Main engine	2 x MAK 2,400 kW
Propulsion system	Twin CPP rudder propellers/azimuth thrusters
Total BHP	6,500 BHP
Bow thruster	2 x 12 t (800 kW) electric driven
Main generator	3 x 500 kW diesel driven
Shaft generator	2 x Leroy Somer 1,230 kW main engine driven
Emergency generator	1 x 95 kW diesel driven

PERFORMANCE

Fuel consumption at 9.5 knots	abt 13 m ³ /day
Fuel consumption at 7.5 knots	abt 10.9 m ³ /day
DP mode	abt 7 m ³ /day
In port	abt 1.8 m ³ /day
General field duties - average	abt 7 m ³ /day
Fuel type	ISO 8217: 2005 DMA or later revisions

EXTERNAL FIRE-FIGHTING

Capacity	ABS Fifi Class 1 - 3,000 m ³ per hr
Monitor	2 x 1,200 m ³ per hr
Throw x height	120 m x 45 m

LIFE-SAVING EQUIPMENT

Life rafts	6 x 25 men and 2 x 15 men
Rescue boat	1 x 6 men rescue boat with 25HP OBM
Scrambling nets	1 on each side of rescue zone

CARGO CAPABILITIES

Fresh water	730 m ³ - 150 m ³ /hr at 80m head
Drill water	1,720 m ³ - 100 m ³ /hr at 80m head
Fuel capacity (100%)	860 m ³ - 150 m ³ /hr at 80m head
Liquid mud / brine / ORO	816 m ³ - 2 x 75 m ³ /hr at 80m head
Brine / ORO (additional)	175 m ³ - 50 m ³ /hr at 9 bar
Dry bulk	222 m ³ (4 x 2,000 ft ³) - 40 m ³ /hr
Foam	27 m ³
Detergent	27 m ³
Clear deck area	750 m ²
Deck cargo	1,500 t
Deck loading	7 t/m ²
Fresh water maker	2 x 10 t per day

COMMUNICATIONS EQUIPMENT

HF radio	Furuno model RC-1800T
VHF radio	Furuno FM-8800S
Portable VHF radio	3 x McMurdo model R2 GMDSS
Satellite E.P.I.R.B.	McMurdo model SMARTFIND E5
Inmarsat	Inmarsat-C with EGC
Navtex receiver	Furuno NX-700A (GMDSS)
SART	2 x McMurdo S4 Rescue SART

NAVIGATION EQUIPMENT

Radar no. 1	Furuno FAR-2117-D, X-Band
Radar no. 2	Furuno FAR-2137S-D, S-Band
GPS	2 x Furuno GP-150
Echo sounder	Furuno FE-700
Auto pilot	Anchutzh Pilot Star-D
Gyro compass	3 x Anschutz Gyro
Magnetic compass	Anschutz Magnetic Standard 22
Dynamic position system	Kongsberg K-Pos DP21
Automatic Identification System (AIS)	Furuno FA-150
Reference system 1	DGNSS 1 - Kongsberg DPS112
Reference system 2	DGNSS 2 - Kongsberg DPS110
Reference system 3	LASER - Guidance Marine CyScan MK4
Reference system 4	RADAR - Guidance Marine RadaScan

DECK EQUIPMENT

Tuggers	2 x 10 t @ 24m/min
Capstans	2 x 10 t @ 25m/min
Deck crane	3 t SWL @ 10m

ACCOMMODATION

Crew	14
Passengers	38
Total	52
Hospital	1

30/01/2023

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented, no guarantees of accuracy can be given. For enquiries, kindly email us at chartering@sg.vroonoffshore.com.