



VOS PURPOSE

Platform-supply vessel

75M DP-2

Vessel number 3232

GENERAL

Flag	Italian
Port of registry	Ancona
Year built	2013
Place built	Fujian South East Shipyard, China
Class	RINA
	Supply vessel; fire-fighting ship - 1 - oil recovery ship; unrestricted navigation; AUT-UMS; dynapos AM - R; LSF 0,1; SPS up to 60
Call sign	IBCU
IMO number	9664225
Vessel type	Platform Supply Vessel DP-2 SPS

PRINCIPAL DIMENSIONS

Length overall (LOA)	75 m
Beam	17.25 m
Maximum draft	6.6 m
Net registered tonnage	939 t
Gross registered tonnage	2,948 t
Deadweight	3,323 t

MACHINERY & PROPULSION

Main propulsion output	6,000 BHP (2 x 3,000 BHP @ 750 rpm)
Main propulsion type	Niigata model 8L 28 HX
Propulsion	2 x Azimuth
Propellers	Z-PELLER NIIGATA
Bow thruster	2 x 650 kW
Main generator	3 x CAT C18 450 kW
Shaft generator	2 Leroy Somer x 1000 kW main engine driven
Emergency generator	1 x CAT C4.4 80 kW
Water maker	2 x 10 m ³ /day

PERFORMANCE

Fuel consumption at 12 knots	abt 13 mt/day
Fuel consumption at 10 knots	abt 9 mt/day
Fuel consumption at 8 knots	abt 7 mt/day
DP mode	abt 6 mt/day
In port	abt 0.5 mt/day
Fuel type	ISO 8217: 2005 DMA or later revisions

CARGO CAPABILITIES

Fresh water	550 m ³ - 100 m ³ /hr at 80m head
Drill water	1,322 m ³ - 100 m ³ /hr at 80m head
Fuel capacity (100%)	775 m ³ - 150 m ³ /hr at 80m head
Liquid mud	739 m ³ - 70 m ³ /hr
Dry bulk	4 SILOS (228 m ³) - 2 x 20 m ³ /min (compressors)
Base oil	147 m ³
Clear deck area	700 m ²
Deck cargo	1,200 t
Deck loading	5.5 t/m ²

COMMUNICATIONS EQUIPMENT

HF radio	Furuno FS-2575C
VHF radio	2 x Furuno FM-8800S
Portable VHF radios	3 x McMurdo R2 GMDSS handheld
Satellite communications	VSAT/IRIDIUM (voice & fax)
E.P.I.R.B.	McMurdo SMARTFIND E5
INMARSAT	INMARSAT "C"
GMDSS compliance	A1+A2+A3

NAVIGATION EQUIPMENT

Radar no. 1	S-Band Furuno FAR-2137
Radar no. 2	X-Band Furuno FAR-2117
Echo sounder	Furuno FE 700
Navtex	Furuno NX 700
Gyro compass	Digital GYRO STD 22 X 3
Doppler speed log	Furuno DS80
Auto pilot	Anchut Pilot Star-D
GPS	Furuno GP 150
A.I.S.	Furuno FA 150
Weather facsimile	Furuno FAX 408
Dynamic position system	DPS-2, Kongsberg, K-POS DP-21 and Cjoy
Reference system 1 & 2	DGPS DPS 110
Reference system 3	Cyscan

DECK EQUIPMENT

Tugger winches	2 x 10 t @ 24m/min
Capstans	2 x 10 t @ 25m/min
Deck crane	1 x 3 t / 9 m

OTHER EQUIPMENT

Anti-pollution equipment-spray booms	
Oil Recovery	
Automated fuel consumption and ROB measurement system	
Coriolis flow meters	

EXTERNAL FIRE-FIGHTING

FiFi Class 1	2 x 1200 cu m per hr
Monitor	2
Throw x height	120 m x 50 m

LIFE-SAVING EQUIPMENT

Life rafts	total 6, capacity 150 men
Rescue boat	28 HP, capacity 6 men, eng. type 380J-3

ACCOMMODATION

Vessel is SPS Classed and allowed to carry up to 60 people, incl. crew, in transit	
Crew accommodation	14
Special personnel	36
Hospital	Yes
Total beds	50

30/01/2023

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented, no guarantees of accuracy can be given. For enquiries, kindly email us at chartering@it.vroonoffshore.com.