# VOS THALIA (3072)



| GENERAL        |  |
|----------------|--|
| Place of Build |  |
| Vessel Type    |  |
| Year Built     |  |
| Flag           |  |
| Call Sign      |  |

Class

Fujian South East Shipyard, China AHTS 2012 Singapore 9V9436 ABS FIFI 1 DPS 1

approx 18 m3 per day @ 13 knots

### **COMMUNICATIONS EQUIPMENT**

Furuno RC-1800T HF radio VHF Radio 2 x Furuno FM-8800S Portable VHF Radio's 3 x McMurdo R2 Handheld Satellite Communications (Voice and Fax) Furuno SAT C E.P.I.R.B McMurdo SMARTFIND E5 **GMDSS** Compliance Area A3

### PRINCIPAL DIMENSIONS

59.25 metres Length Overall Beam 14.95 metres Maximum Draft 4.95 metres Net Registered Tonnage 503 Gross Registered Tonnage 1678

#### **NAVIGATION EQUIPMENT**

X-Band Furuno FAR-2117 Radar No. 1 Radar No. 2 X-Band Furuno FR-1510 MARK-3 GP 150 GPS Furuno FE 700 Echo Sounder NX 700 Navtex Nautopilot NP 60 Auto Pilot Gyro Compass Anchutz STD 22 DP System Marine Tech

## MACHINERY & PROPULSION

Main Propulsion Number 2 Main Propulsion Type CAT 3516B Diesel Total BHP 5150 Propellers 2 x CPP in Fixed Kort Nozzles 1 x Kawasaki KT-55B3-390KW-6T thrust Bow Thruster Main Generators 3 x 350 KW diesel driven **Emergency Generators** 1 x 65kW diesel Rudders Standard

### **DECK MACHINERY**

2 x 10 tons @ 15m/min Tugger Winch Capstan 2 x 5 tons @ 15m/min . Deck Crane 1 x 3 tonnes @ 9 m

#### **PERFORMANCES**

Fuel Consumption at Max Speed

approx 10 m3 per day @ 10 knots Fuel Consumption at Service Speed Towing approx 20 m3 per day Standby approx 1 m3 per day Fuel Type ISO 8217: 2005 DMA or later revisions CARGO CAPABILITIES Fresh Water 300 m3 @ 100m3 per hr at 75m head 400 m3 @ 100m3 per hr at 75m head Drill Water Fuel Capacity (100%) 540 m3 @ 150m3 per hr at 75m head Liquid Mud 385 m3 @ 70m3 per hr Dry Bulk 4 X 1650 cu ft each, total 6,600 cu ft Dead Weight 1400 tons Clear Deck Area 340 Square Metres 500 tons Deck Cargo 7.5 tonnes/sqm **Deck Loading** 

## **TOWING & ANCHOR HANDLING**

Bollard Pull 69.9 tons Winch Mentrade Waterfall Type Line Pull 150 tons **Brake Capacity** 200 tons Anchor Handling Wire and Towing Wire 100m and 1000m - 56mm Anchor Handling Wire Capacity 150 m x 56 mm 1000 m x 56 mm Tow Drum Capacity Spare Tow Wire Capacity 1000 m x 56 mm 4.4 m x 1.6 m - SWI 200 tonnes Stern Roller Tow Pins 2 x Closed Top Type - 200T SWL Shark Jaws 1 set of Karmfork - 200T SWL LIFE SAVING APPARATUS

Total 6, capacity 150 men Liferafts 25 HP OBM, capacity 6 men Rescue Boat

## ACCOMMODATION

Crew 12 Passengers 28 (4 x 1-berth, 3 x 2-berth, 8 x 4-berth) Total 40

## **EXTERNAL FIRE FIGHTING**

FIFI 1 - 2400 cu m per hr Capacity 2 x 1200 cu m per hr Monitor Throw x Height 120 m x 50 m

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented, no guarantees of accuracy can be given. For enquires, kindly email us at <a href="mailto:chartering@sg.vroonoffshore.com">chartering@sg.vroonoffshore.com</a>





