

VOS Faithful Emergency response and rescue vessel

Vessel number 3422

GENERAL	
Survivor Class	Group 'B' (300 survivors)
Builder	Jiangsu Island, Nanjing , China
Vessel type	ERRV
Year built	2014
Port of registry	Aberdeen
Flag	United Kingdom
Call sign	2GGZ5
Class	Lloyd's Register

PRINCIPAL DIMENSIONS	
Length overall (LOA)	50 m
Beam	13.20 m
Summer draft	3.75 m
Net registered tonnage	397
Gross registered tonnage	1,325
Freeboard at rescue zone	<1.75 m

MACHINERY & PROPULSION	
Main propulsion number	2
Main propulsion power source	Mechanical marine diesel Caterpillar
Main propulsion type	2 x variable pitch propeller
Total power output	1,640 kW
Side thrusters number	1
Side thrusters type	Retractable azimuth, bow thruster
Side thruster power source	Electrical
Side thruster power output	440 kW
Rudders	2

PERFORMANCE	
Fuel consumption at max speed	Approx. 5 tonnes per day @ 12 knots
Fuel consumption at economic speed	Approx. 3 tonnes per day @ 10 knots
Fuel consumption in standby mode	<1 tonne per day

ADDITIONAL CAPABILITIES		
Water capacity	200 m3	
Fuel capacity	250 m3	
Dispersant booms	2	
Dispersant pumping system	Grundfoss Pump 6m³ / hr	
Dispersant capacity	5 tonnes	
Dispersant type	Client's supply	
Bollard pull	N/A	
Towing arrangements	Emergency towing only	

ACCOMMODATION	
Crew accommodation	15 cabins (8 singles + 7 doubles)
Total crew accommodation capacity	22
Number of seats (survivors)	66
Number of bunks (survivors)	26

COMMUNICATIONS EQUIPMENT		
MF radio	Yes	
VHF radio	Yes	
Portable VHF radios	Yes	
Broadband	Yes	
Satellite communications (voice and fax)	Yes	
Email	Yes	
Mobile phone	Yes	
E.P.I.R.B.	Yes	
S.A.R.T. (no. and type)	2	
Hospital communications	Yes	
UHF radio 1	Yes	
GMDSS compliance	Yes	

Yes Yes Yes
Yes
Yes

SURVIVOR RECOVERY/RESCUE EQUIPMENT	•
Rescue craft no 1 type	Kossen 15 person daughter craft
Davit no. 1 type	MacGregor HMD G40
Davit no. 1 safe working load (SWL)	4 metric tonnes
Davit no. 1 secondary lift	Electric/hydraulic
Rescue craft no. 2 type	Kossen 15 person fast rescue craft
Davit no. 2 type	MacGregor HMD G40
Davit no. 2 safe working load (SWL)	4 metric tonnes
Davit no. 2 secondary lift	Electric/hydraulic
Additional rescue craft	Can be fitted on request

ADDITIONAL RESCUE/RECOVERY FACILITIES	
Mechanical recovery type	Dacon Scoop
Overside rescue zones size	2 x 5 mt
Emergency helicopter winching area	Yes
Rescue basket	1x6 man
Searchlights	2
Vessel self-drenching capacity	Yes
Fire monitors - number	N/A
Fire monitor throw	N/A
Monitors total capacity	N/A

18/09/2022

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented, no guarantees of accuracy can be given. For enquiries, kindly email us at chartering@uk.vroonoffshore.com.





