

GENERAL Flag Dutch Port of registry Breskens Builder Fujian, China 2016 Year built LR X 100 A1 Offshore Supply Ship, Class ECO(TOC), LMC, UMS, DPA(AA)SPS, DPS-2 IMO 9697131 Call sign PDCT ERN number 99.99.73.63 MMSI 244820666 PRINCIPAL DIMENSIONS Length overall (LOA) 68.04 m Breadth moulded 14.95 m Length B.P.P. 61.49 m Depth (MLD) 6.1 m Summer draught 5.00 m 2,030 t Gross registered tonnage Net tonnage 609 t Deadweight 1,712 mt TANK CAPACITIES MGO 510 m³ Potable water 380 m³ Water ballast 1,020 m³ Heeling tanks 112 m³ Ballast water (BWTS) yes MACHINERY & PROPULSION 2 x CAT 3516B 1,920 kW with CPP Main propulsion (2,575 BHP) 1 x CAT C18 550 kW (737 BHP) Auxiliary engines 2 x CAT C32 715 kW (960 BHP) Bow thrusters 1 x Tunnel thruster FPP 600 kW & 1 x FPP retractable 500 kW Stern thrusters 2 x Tunnel thruster CPP 400 kW Shaft generator 2 x 1,000 kW **Emergency generator** 1 x CAT C6.6 158 kW PERFORMANCE/FUEL CONSU MPTION Full speed (13 knots) 15 mt/day Service speed (11 knots) 11 mt/day DP mode 7 mt/day Idle in port 1 mt/day ACCOMMODATION/OFFICES/ ACILITIES Total accommodation 49 27 Charterer's accommodation 22 Crew accommodation Gym 1 **Recreation room** 1 Smoking room 1 Offices 3 Compliance MLC 2006

VOS STAR	
Subsea-support vessel	
58M DP2	

	Vessel number 3314	
LIFE-SAVING EQUIPMENT		
Life rafts	6 x 25 men	
Scrambling nets	1 x set scrambling nets	
DYNAMIC POSITIONING		
DP class	Kongsberg DP2	
Gryo compass	3 x Gyro compass	
DGPS	1 x DPS 110 / 1 x DPS 112	
Taut wire	LTW Bandak MK 15	
Hipap 500	Kongsberg	
CyScan	1 x Kongsberg	
Motion sensors (MRU)	2 x Kongsberg	
Wind sensors	3 x Kongsberg	
NAVIGATIONAL EQUIPMENT		
Radar no.1	1 x X-Band radar	
Radar no.2	1 x S-Band radar	
Eco sounder	1	
Auto pilot	1	
Magnetic compass	1	
Joystick control	1	
Electric chart display	1 x ECDIS	
DECK AREA AND SERVICES		
Clear deck space	485	
Deck strength	7 mt / m2	
Deck cargo	350 t	
Bulwark (removable)	2 x port & 1 x starboard side	
	along work deck	
Power connections	1 x 63A (440V, 3 phase, 60 Hz)	
CRANE-LIFTING EQUIPMENT		
Main crane	SMST knuckle boom	
Max hoist wire	370 m / 30 mm diam.	
Max. outreach with AHC	AHC: 6 t @ 19 m	
	AHC: 12 t @ 13 m	
	Double hoist: 24 t @ 8 m	
Crane jib extension	2 t @ 30 m height	
(charterer's request)	with 25 m outreach	
Deck store/Aux crane	3 t SWL @ 9 m	
Capstans	2 x 5 t @ 15 m/min	
COMMUNICATIONS FACILITIES		
MF/HF radio	1 x Furuno FS 2575C	
VHF radio	2 x Furuno FM-8900S	
Portable two-way VHF	3 x portable two way GMDSS VHF	
Satellite EPIRB	1 x satellite EPIRB Ocean signal E100	
Navtex receiver	1 x Furuno Navtex receiver NX700	
SART	2 x SART Ocean Signal Sart 100	
Satellite communication	Furuno Felcom 18	
Automatic identification	1 x AIS FA-150	
FACILITIES FOR OFFSHORE PI		
Boat landing for offshore personnel transfer (OPTIONAL)		

FACILITIES FOR FUEL DELIVERY

Pumping rate up to 6,000 litre/hr @30 m height TODO Connections on deck

08-12-2022

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented, no guarantees of accuracy can be given. For enquiries, kindly email us at chartering@nl.vroonoffshore.com.

VROON OFFSHORE SERVICES

www.vroonoffshore.com chartering@nl.vroonoffshore.com operations@nl.vroonoffshore.com

